



RV Investigator Voyage Plan

Voyage #:	IN2021_E03
Voyage title:	Equipment Trials and Calibrations 2021
Mobilisation:	Monday, 29 November 2021, Hobart PW04
Medical clearance:	Tuesday, 30 November to Wednesday, 1 December 2021, Hobart PW04
Depart:	Wednesday, 1 December 2021, Hobart PW04, 1000hrs
Return:	Wednesday, 8 December 2021, Hobart PW04, 0800hrs
Demobilisation:	Wednesday 8 to Friday 10 December 2021, Hobart PW04
Voyage Delivery Coordinator	David Flynn
Voyage Manager:	Tegan Sime
Deputy Voyage Manager:	David Flynn
Technical Lead:	Jason Fazey
Affiliation:	CSIRO – MNF

Scope Of Works: Both Voyages:

Team	Activities Targeted	Time Requested / Required	Limitations / Constraints / Requirements	Day / Night Operations	Ideal Water Depth Operations	Comments:
Field Operations (FO) + ASP Crew	New Core Handling (OSIL) Trials + Giant Piston Coring (TRIPLEX) / Trials New Kasten Coring System Trials	8hrs Core Handler Handshake Tests + ~12hrs ea. 4.8m core, x3 ~14hrs ea. 14.4m core, x1 12hrs ea. , x2	Core Handler practice 4hrs each shift + Short cores then long core ~2hrs to swap rollers	Daylight only	Target 1500–3000m Deeper operations take longer, dependant on sub-bottom profile interpretation from GA As above	On-ship advice required from geoscientist (GA). Off-ship contact with OSIL for core handling.
Geophysical Survey and Mapping (GSM)	Reference Surface Checks (EM122 & EM710) Drop Keel Calibrations Opportunistic Mapping	8hrs (Reciprocal Lines) 2hrs (Stop/Start) Ad Hoc	Lines @6kts Ad Hoc Ad Hoc	N/A N/A Night	Known Locations Targeted >3000m >1500m water depth (mimic transit) N/A	Flat gradient bathymetry required Opportunistic testing between stations N/A
Data Acquisition and Processing (DAP)	New & Existing Staff cross-training + PABX Phone Upgrade Testing Misc. upgrades/tests	0hrs	N/A	N/A	N/A	No dedicated ship time required or system outages/interruptions expected.
Seagoing Instrumentation Team (SIT)	“Drop-Tow” Camera (MkII DTC configured to drop camera)	Ad Hoc	Reconfigure DTC bridle & camera mounts	Night		

Voyage objectives

The primary voyage objective for these voyages, are for the Marine National Facility (MNF) to calibrate and commission new, upgraded and existing critical equipment (with sea trials and personnel training) onboard *RV Investigator* for upcoming voyages in the 2021 schedule and beyond.

Specifically, work will focus on the seagoing testing and trials of MNF's new Giant Piston Corer with 24m maximum barrel length capability, principally supported by the Geophysical Survey and Mapping team and marine geoscientists from UTAS.

Additionally the voyage will finalise the calibration of the CTD#2 winch with Rapp Macgregor personnel, crew and support staff.

Ancillary Objectives (Piggybacks)

The following ancillary voyage objectives are targeted where they don't limit or impact above priorities.

- 1) A small contingent of scientists will advise on QAQC for collection of piston coring samples. The scientific advisors have supported voyage planning by advising appropriate sites of interest that target reduced risks to equipment and personnel, aid commissioning and gain scientific insight, notable thanks to Alix Post and Scott Nichol from Geoscience Australia. Due to traveling restrictions, Martin Jutzeler and Acacia Clark have agreed to fill in this QAQC role onboard the voyage. If cores are successful and of scientific value, they will be provided to the scientific advisors for analysis post voyage in accordance with [CSIRO's Data and Sample Management Policy](#).
- 2) Underway aerosol particulate CO₂ sensor upgrade & replacement, testing & monitoring underway by Craig Neill from O&A.

Voyage Risk Assessment (VRA)

A Voyage Specific Risk Assessment (VSRA) has been created for IN2021_E03. ASP has a number Job Safety Environment Analyses (JSEAs) that ensure each voyage's risks have been identified and appropriately controlled. ASP also maintains a service contract with the Original Equipment Manufacturer (OEM) RAPP MacGregor and Ocean Scientific International Ltd. (OSIL), contracted to provide ongoing OEM support with regard to maintenance, calibration, and equipment repairs.

Overall Activity Plan First 72hrs of Voyage

The following initial activity plan is indicative only. For further and more accurate detail, refer to the: "at sea task activity schedule". Due to the dynamic nature of trials, calibrations and sea state/weather, alternative activities will be undertaken as required.

Day	Date	Time	Activity
Tuesday-Wednesday	30 Nov-1 Dec	0800	Crew: Phase 3 Test and pre-voyage medical clearance period
Wednesday	1 Dec	~1000	Sail from PW04 Hobart
Wednesday	1 Dec	1200	CPH/GPC testing and familiarisation for crew
Thursday	2 Dec	0600	Commence Piston Coring activities

Voyage track example

Figure 1. IN2021_E03 proposed voyage track in Green, with track waypoints and commonwealth marine parks shown.




Figure 2. Excerpt of GSM report on Sub Bottom Profile data analysing options for best coring sample location.

Waypoints, stations & time estimates

SITE / WAYPOINT	LATITUDE DD	LONGITUDE DD	DISTANCE (NM)	TOTAL DISTANCE (NM)	STEAMING TIME (HRS)	TOTAL STEAM (HRS)
Hobart Princes Wharf #04	-42.88644	147.33872	0	0	0	0
Tranmere	-42.92144	147.39033	3.1	3.1	0.5	0.5
White Rock Point	-42.97330	147.37760	3.2	6.3	0.5	10.9
Storm Bay	-43.10647	147.40961	0.0	6.3	0.0	1.0
GSM/GA Coring Option "A"	-43.23280	148.64280	31.1	63.1	3.0	6.7
Storm Bay	-43.10647	147.40961	11.0	120.0	1.4	13.8
White Rock Point	-42.97330	147.37760	8.1	128.1	1.4	10.9
Tranmere	-42.92144	147.39033	3.2	131.2	0.8	16.0
Hobart Princes Wharf #04	-42.88644	147.33872	3.1	134.3	0.8	16.8

Proposed Activity Plan

Waypoint	Activity	Depth (m)	Time (activity end)
Hobart Princes Wharf #04	Departure	10	2/12/2021 11:00
Tranmere	Piloted Transit	10	
White Rock Point	Core handling familiarisation am. swing	35	2/12/2021
White Rock Point	Core handling familiarisation p.m. swing	35	2/12/2021
Storm Bay	Transit (~7 hours) to first site	30	2/12/2021
CTD#2 wire calibration @ 4hrs	TBD (based on conditions not positive for coring)	3238	3/12/2021
GSM/GA Coring Option "A"	Piston core #1 full end to end operation (commissioning) - 9.6m barrel	3238	3/12/2021
GSM/GA Coring Option "A"	Night time SBP & mapping	3238	
GSM/GA Coring Option "A"	Kasten Coring (#1) x1 Deployment	3238	4/12/2021
GSM/GA Coring Option "A"	Night time SBP & mapping	3238	
GSM/GA Coring Option "A"	Piston Coring Barrel (9.6m) #2 Deployment (FO swing A&B)	3238	5/12/2021
GSM/GA Coring Option "A"	Night time SBP & mapping	3238	
GSM/GA Coring Option "A"	Kasten Coring (#2) x1 Deployment	3238	6/12/2021
GSM/GA Coring Option "A"	Piston Coring Barrel (14.4m) #1 Deployment	3238	7/12/2021
GSM/GA Coring Option "A"	Kasten Coring (#3) x1 Deployment	3238	8/12/2021
Storm Bay	Transit	30	8/12/2021
White Rock Point	Transit	35	
Tranmere	Piloted Transit	10	
Hobart Princes Wharf #04	ETA Hobart PW4 at ~0800hrs	10	9/12/2021

Permits & Notifications

- Australian Marine Parks blanket permit (Permit Number: **PA2020-00041-2**; 24 June 2020 to 20 August 2023) covers the MNF for all planned underway science activities within commonwealth marine parks, as listed in this voyage plan. No other activities requiring further permits are planned within commonwealth marine parks for this voyage (e.g. rock dredging, hydrabios net sampling, CTD water retention).

Signature

Your name	Jason Fazey
Title	Technical Lead
Signature	Jason Fazey
Date:	1 December 2021

List of additional figures and documents

- a. Appendix A: Selected MNF Equipment List
- b. Special Requests MNF Scientific Equipment and Facilities
- c. Appendix B: User Supplied Equipment

Appendix A

Scientific equipment and facilities provided by the Marine National Facility

Some equipment items on the list may not be available at the time of sailing. Applicants will be notified directly of any changes. Indicate what equipment and facilities you require from the Marine National Facility by placing an **X** in the relevant box.

STANDARD LABORATORIES AND FACILITIES		
NAME	REQUIRED	NOTES/COMMENTS
Aerosol Sampling Lab		<ul style="list-style-type: none"> Please indicate the intended activity in this lab
Air Chemistry Lab		<ul style="list-style-type: none"> Please indicate the intended activity in this lab
Preservation Lab		<ul style="list-style-type: none"> Please indicate the intended activity in this lab
Constant Temperature Lab (Min temp: 2°C / Max temp 35°C)	X	<ul style="list-style-type: none"> Storage of extruded successful cores 2°C as desired setpoint for temperature
Underway Seawater Analysis Laboratory	X	<ul style="list-style-type: none"> PCO² (Carbon Dioxide Sensor) Calibration and Testing of new sensor underway
GP Wet Lab (Dirty)	X	<ul style="list-style-type: none"> General Activities
GP Wet Lab (Clean)		<ul style="list-style-type: none"> Please indicate the intended activity in this lab
GP Dry Lab (Clean)		<ul style="list-style-type: none"> Please indicate the intended activity in this lab
Sheltered Science Area	X	<ul style="list-style-type: none"> Core Cutting, Extruding, Handling, Processing.
Observation Deck 07 Level		<ul style="list-style-type: none"> Please indicate the intended activity in this area
Internal Freezer (Dirty Wet lab) (Min temp -25°C / Max temp 0°C) Volume: >20m ³		<ul style="list-style-type: none"> Please indicate the intended activity in this area Please indicate the required setpoint temperature
Clean Freezer (Dirty Wet lab) (Min temp -25°C / Max temp 0°C) Volume: >2.5m ³ Co-located within the Internal freezer and separated by a door		<ul style="list-style-type: none"> Please indicate the intended activity in this area Please indicate the required setpoint temperature

STANDARD LABORATORIES AND FACILITIES		
NAME	REQUIRED	NOTES/COMMENTS
Blast Freezer (Dirty Wet lab) (Min temp -30°C / Max temp 0°C) Internal volume >1.5m ³ Capable of reducing the temperature of 150kg of water from +20C to -30C in one hour.		<ul style="list-style-type: none"> • Please indicate the intended activity in this area • Please indicate the required setpoint temperature
Cool Room (Dirty Wet lab) (Min temp 0°C / Max temp 10°C)		<ul style="list-style-type: none"> • Please indicate the intended activity in this area • Please indicate the required setpoint temperature
Ultra-Low Temperature Freezers x2 (Main Deck) Min temp -80°C / Max temp -80°C)		<ul style="list-style-type: none"> • Please indicate the intended activity in this area
YODA Freezers (x2) (Clean Dry lab) (Min temp -20°C / Max temp 10°C)		<ul style="list-style-type: none"> • Please specify if both or only one are needed • Please indicate the intended activity in this area • Please indicate the required setpoint temperature

MOBILE LABORATORY AND FACILITIES (MAY REQUIRE ADDITIONAL SUPPORT)			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS
Modular Isotope Laboratory			If nominated, additional processes to be completed.
Trace Metal Niskin Sampling Container (TM1-blue)			
Trace Metal Seawater Analysis Laboratory (TM2-white)			Cannot be overstacked
Trace Metal Rosette and Niskin Storage Container			10-foot container
Modular Hazchem Locker			
Stabilised Platform Container			Please indicate what instruments are to be installed in the container Cannot be overstacked
Clothing Container			The use of this container will be identified by MNF

STANDARD SAMPLING EQUIPMENT			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS
CTD - Seabird 911 with 36 Bottle Rosette			N/A
CTD - Seabird 911 with 24 Bottle Rosette			N/A
Lowered ADCP			
Continuous Plankton Recorder (CPR)			

SPECIALISED SAMPLING EQUIPMENT			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS (THESE ITEMS MAY REQUIRE ADDITIONAL MNF SUPPORT STAFF)
TRIAXUS – Underway Profiling CTD			Triaxus is a pilotable towed vehicle capable of carrying a variety of instrumentation. Constant depth towing or undulating profiles (e.g. cyclic depth pattern from the surface to 200m) are possible. Towing speed depends on the tow profile, instrumentation payload and prevailing conditions. Typically, undulations from the surface to 200m are possible at 8knt, with slower speeds for deeper profiles and faster for constant-depth towing. Maximum achievable depth typically 300m Usual instrumentation: SBE9plus (pressure sensor and communication hub) and dual pumped temperature/conductivity/dissolved oxygen circuits. Usual auxiliary instrumentation includes an ECO-Triplet (Chl, CDOM, backscatter), transmissometer, PAR sensor, and Laser Optical Plankton Counter. Contact MNF for further details on other instrumentation and capability.
Desired towing profile:			
Additional instrumentation: (please supply, make and model and datasheets and a contact person for discussion on integration)			
Piston Coring System	X		
Gravity Coring System		X	
Multi Corer			

SPECIALISED SAMPLING EQUIPMENT			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS (THESE ITEMS MAY REQUIRE ADDITIONAL MNF SUPPORT STAFF)
Kasten Corer	X		New Kasten Core system running from piston core cradle (rather than stern deployment)
Smith Mac Grab	X		
Rock Dredges			
Rock Saw			Requires trained science personnel
Seaspy Magnetometer	X		
Portable Pot Hauler			
Equipment to measure seawater sound velocity/CTD:	X		
XBT System	X		2 per day provided
Valeport Rapid SV	X		
Valeport Rapid CTD	X		
Valeport SVX2			
Trace Metal Rosette and Bottles			
Trace Metal In-situ Pumps (x6)			See non-MNF owned section below for additional 2 units
Deep Towed Camera			
Drop Camera			
Sherman Epibenthic Sled			
Brenke Sled			
EZ Net (Multiple net system, 1m x 1m)			Please specify 335-micron, 500-micron, or 1,000-micron mesh
Hydro-Bios MultiNet (1m x 1m)			Please specify 335-micron, 500-micron, or 1,000-micron mesh
Surface Net (1m x 1m)			Please specify 335-micron, 500-micron, or 1,000-micron mesh
Bongo Net 485mm diameter			500 micron mesh only
Beam Trawl			
MIDOC			Multiple opening/closing net system with cod ends- suitable for pelagic trawls
Pelagic Trawl System (net, doors)			Contact MNF to discuss net and mesh dimensions
Demersal Trawl System (net, doors)			Contact MNF to discuss net and mesh dimensions

SPECIALISED SAMPLING EQUIPMENT			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS (THESE ITEMS MAY REQUIRE ADDITIONAL MNF SUPPORT STAFF)
RMT-8 (Rectangular Midwater Trawl) Utilises a single warp so can be deployed on the general-purpose towing wire in self-contained mode. Must be deployed with stern ramp covered.			8m ² mouth area Tow speed ≤2 knots
RMT-16 (Rectangular Midwater Trawl) Utilises a single warp so can be deployed on the general-purpose towing wire in self-contained mode. Must be deployed with stern ramp covered.			16m ² mouth area Tow speed ≤2 knots
Trawl Monitoring Instrumentation (ITI) (2,000m depth limit)			MNF to identify this need, dependent on pelagic or demersal trawling requirement
Stern ramp	INSTALLED		MNF to identify this requirement

RESEARCH SUPPORT INFRASTRUCTURE			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS
Salt Water Ice Machine (Dirty Wet lab)			
Radiosonde Receiver System			
Laboratory Incubators (Clean Dry lab)			
Deck Incubators			Temperature controlled deck incubators
Milli-Q System			
Sonardyne USBL System			

SCIENTIFIC / SAMPLE ANALYSIS SYSTEMS				
MICROSCOPES:				NOTES/COMMENTS
BRAND / MODEL	TYPE	ESSENTIAL	DESIRABLE	Refer to the "MNF microscopes procedure" for more information
Leica / M80	Dissecting			
Leica / M80	Dissecting			
Leica /MZ6	Dissecting			
Olympus / CH	Compound			
Olympus /CH	Compound			
Leica / MTU282	Camera tube			
Adapters for tube / Nikon	Pentax			
Ring Light *2 / MEB121	LED			
Heavy Duty Electronic Balance (80kg)				
Medium Duty Electronic Balance (15kg/5g resolution)				
Light Duty Electronic Balance (3kg/1g resolution)				

Underway systems

ACOUSTIC UNDERWAY SYSTEMS			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS
75kHz ADCP			
150kHz ADCP			
Multi Beam Echo Sounder EM122 12kHz (100m to full ocean depth)	X		
Multi Beam Echo Sounder EM710 70-100kHz (0-1000m approx.)	X		
Sub-Bottom Profiler SBP120	X		
Scientific Narrowband Echo Sounders EK60 (6 bands, 18kHz-333kHz)	X		EK60s will be onboard for use as a backup for EK80s and set in narrowband mode Quantitative measurements from scientific echosounders requires sphere calibration in the watermass of sampling

ACOUSTIC UNDERWAY SYSTEMS			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS
Scientific Narrowband/Broadband Echo Sounders EK80 (6 bands, 18kHz-333kHz)	X		EK80s will be used in narrowband mode unless otherwise requested Quantitative measurements from scientific echosounders requires sphere calibration in the watermass of sampling
Multibeam Scientific Echo Sounder ME70 (70-100 kHz)			
Omnidirectional Echo Sounder SH90			
Gravity Meter	X		

ATMOSPHERIC UNDERWAY SENSORS			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS
Nephelometer			
Multi Angle Absorption Photometer (MAAP)			
Scanning Mobility Particle Sizer (SMPS)			
Radon Detector			
Ozone Detector			
Condensation Particle Counter (CPC)			
Picarro Spectrometer (analysis of CO ₂ /CH ₄ /H ₂ O)			
Aerodyne Spectrometer (analysis of N ₂ O/CO/H ₂ O)			
Cloud Condensation Nuclei (CCN)			
Polarimetric Weather Radar			

UNDERWAY SEAWATER SYSTEMS AND INSTRUMENTATION			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS
Thermosalinograph			
Fluorometer			
Optode			
pCO ₂	X		PCO ₂ (Carbon Dioxide Sensor) Calibration and Testing of new sensor underway

SEAWATER SYSTEMS			
NAME	ESSENTIAL	DESIRABLE	NOTES/COMMENTS
Trace metal clean seawater supply			
Scientific clean seawater supplied to laboratories		X	
Raw seawater available on deck and in laboratories	X		

EQUIPMENT AND SAMPLING GEAR REQUIRING EXTERNAL SUPPORT (MAY REQUIRE ADDITIONAL SUPPORT FROM APPLICANTS)			
NAME	ESSENTIAL	DESIRABLE	PLEASE GIVE THIS CAREFUL CONSIDERATION, AS THERE IS NO GUARANTEE THAT THESE RESOURCES WILL BE AVAILABLE UNLESS SPECIFICALLY REQUESTED. LIAISE WITH YOUR VOYAGE OPERATIONS MANAGER AS REQUIRED. ADDITIONAL STAFF MAY BE REQUIRED FOR THESE ACTIVITIES.
Seismic Compressors			
Seismic Acquisition System			

NON-MNF OWNED EQUIPMENT WHICH MAY BE ACCESSED			
NAME	ESSENTIAL	DESIRABLE	PLEASE GIVE THIS CAREFUL CONSIDERATION, AS THERE IS NO GUARANTEE THAT THESE RESOURCES WILL BE AVAILABLE UNLESS SPECIFICALLY REQUESTED. LIAISE WITH YOUR VOYAGE OPERATIONS MANAGER AS REQUIRED. ADDITIONAL STAFF MAY BE REQUIRED FOR THESE ACTIVITIES.
D & N Francis winch			15mm electro-optical cable
Box Corer			
UTAS In-Situ Pumps (x2)			
EM2040			Shallow water multibeam echosounder system

Appendix B

User Supplied Equipment

Item name	Weight	Dimensions	Location on Vessel
GPC	30 Tonnes	20m ³	Inboard Starboard Gunnels (Core Handler), Back Deck Corer head & sheaves.
CO ₂ spectrometer	15 kg	case 80x53x34 cm instrument 44x44x20 cm	underway seawater lab
CO ₂ spectrometer	10 kg	50 x 32 x 17 cm	underway seawater lab
CO ₂ spectrometer	10 kg	50 x 32 x 17 cm	underway seawater lab
panel PC	5 kg	case 59 x 35 x 24 cm PC 40x40x10 cm	underway seawater lab

Appendix C

Hazardous Materials Manifest

No hazardous materials are planned to be taken or used onboard.