

# RV *Investigator* ADCP Processing Report

Voyage:	IN2022_V02	
Voyage title:	Sedimentation at its extreme: how powerful are submarine caldera- forming eruptions (Kermadec arc)?	
Depart:	Hobart, 10:00 Saturday 19 <sup>th</sup> March 2022	
Return:	Hobart, 10:40 Tuesday 19 <sup>th</sup> April 2022	
Chief Scientist:	Dr Martin Jutzeler	
Affiliation:	CODES/Earth Sciences, UTAS	
ADCP Processing:	V. Dirita	

## **Document History**

Date	Version	Author	Comments
23/06/2022	1.0	Vito Dirita	Initial version
04/07/2022	1.1	Vito Dirita	Pre Release version
28/07/2022	1.2	Vito Dirita	Final Version



#### Contents

Sun	nmary	3
Pro	cessing Background	3
Pro	cessing Notes	3
Are	a Covered	3
net	CDF Data Headers	5
5.1	in2022_v02_os75nb.nc	5
.2	in2022_v02_os150nb.nc	8
	Sun Pro Pro Are net 5.1 5.2	Summary Processing Background Processing Notes Area Covered netCDF Data Headers

#### **1** Summary

The voyage focused its attention on the collection of data and samples around the Kermadec Islands, specifically three massive underwater caldera volcanoes (Macauley, Havre and Healy) to determine their internal structures to infer eruption styles and their depositional processes.

The aim of the voyage was to link the behaviour of deep submarine eruptions with the morphology of their deposits. Modelling calculations of sediment mass fluxes will permit the first-ever hazard mapping scheme for submarine volcanoes globally (tsunami and sediment flow) and provide new ore vectoring strategies for exploration in Australia.

The ADCP was run for most of the voyage, excluding a section where it was requested that data gathering be stopped while permission was granted by the traditional owners. Note that there is no data between the 26<sup>th</sup> March 05:00 to 29<sup>th</sup> March 07:00 UTC.

Data was collected using UHDAS and post-processed using CODAS. Both the RDI Ocean Surveyor 150kHz ADCP and the RDI Ocean Surveyor 75kHz ADCP were run in narrowband. Internal triggering was used. The drop keel was at 8m below the waterline for the duration of the voyage.

See the voyage computing and electronics report for more details regarding data acquisition.

### 2 Processing Background

The University of Hawaii's CODAS software codas\_focal\_20.04\_vbox64.ova was used for processing.

### **3** Processing Notes

Only minor editing was required, Data was masked where instrument anomalies were suspected and where the os75 and os150 data differed significantly. A heading correction was applied to both ADCPs using patch\_hcorr.py using bottom track:

Amplitude and phase rotation corrections applied:

09	575	OS1	150
Amplitude	Phase	Amplitude	Phase
0.9963	0.0575	1.0048	0.0052

Final bottom track amplitude and phase:

05	575	OS1	150
Amplitude	Phase	Amplitude	Phase
1.0001	-0.0020	1.0000	-0.0019

When processing the data, the true transducer offsets in metres from the GPS position of the ship in (meters) are as follows:

05	575	OS	150
dx (m)	dy (m)	dx (m)	dy (m)
-1.0	4.0	-1.0	1.0

### 4. Area Covered



IN2022\_V02 Voyage Track

During a small part of the voyage: 5<sup>th</sup> April 07:25 – 07:55 (1/2 hour) the POSMV failed resulting in bad data which has subsequently been removed (see figure below):



#### **4 netCDF Data Headers**

#### 4.1 in2022\_v02\_os75nb.nc

```
netcdf in2022_v02_os75nb {
dimensions:
       time = 8023;
       depth_cell = 60 ;
variables:
       int trajectory ;
               trajectory:standard_name = "trajectory_id" ;
       double time(time) ;
               time:long_name = "Decimal day" ;
               time:units = "days since 2022-01-01 00:00:00" ;
               time:C format = "%12.5f" ;
               time:standard_name = "time" ;
               time:data_min = 76.9598148148148 ;
               time:data_max = 107.938310185185 ;
       double lon(time) ;
               lon:missing_value = 1.e+38 ;
               lon:long_name = "Longitude" ;
               lon:units = "degrees_east" ;
               lon:C_format = "%9.4f" ;
               lon:standard_name = "longitude" ;
               lon:data_min = 147.352311111111 ;
               lon:data_max = 181.433786111111 ;
       double lat(time) ;
               lat:missing_value = 1.e+38 ;
               lat:long_name = "Latitude" ;
               lat:units = "degrees_north" ;
               lat:C_format = "%9.4f" ;
               lat:standard_name = "latitude" ;
               lat:data_min = -43.283975 ;
               lat:data_max = -29.73386388888889 ;
       float depth(time, depth_cell) ;
               depth:missing_value = 1.e+38f ;
               depth:long_name = "Depth" ;
               depth:units = "meter";
               depth:C_format = "%8.2f" ;
               depth:positive = "down" ;
               depth:data_min = 29.99f ;
               depth:data_max = 973.99f ;
       float u(time, depth_cell) ;
               u:missing_value = 1.e+38f ;
               u:long_name = "Zonal velocity component" ;
               u:units = "meter second-1" ;
               u:C_format = "%7.2f" ;
               u:data_min = -0.6650543f ;
               u:data_max = 1.426992f ;
       float v(time, depth_cell) ;
               v:missing_value = 1.e+38f ;
               v:long_name = "Meridional velocity component" ;
               v:units = "meter second-1" ;
               v:C_format = "%7.2f" ;
               v:data_min = -0.8466916f ;
               v:data_max = 0.7349305f ;
       short amp(time, depth_cell) ;
               amp:missing_value = 32767s ;
               amp:long_name = "Received signal strength" ;
               amp:C_format = "%d" ;
               amp:data_min = 25s ;
               amp:data_max = 217s ;
       byte pg(time, depth_cell) ;
               pg:missing_value = -1b ;
               pg:long_name = "Percent good pings" ;
pg:C_format = "%d" ;
               pg:data_min = 0b ;
               pg:data_max = 100b ;
       byte pflag(time, depth_cell) ;
               pflag:long_name = "Editing flags" ;
               pflag:C_format = "%d" ;
               pflag:data_min = 0b ;
               pflag:data_max = 6b ;
       float heading(time) ;
               heading:missing_value = 1.e+38f ;
```

```
heading:long name = "Ship heading" ;
              heading:units = "degrees" ;
              heading:C_format = "%6.1f";
              heading:data_min = -179.9425f ;
              heading:data_max = 179.9197f ;
       float tr_temp(time) ;
              tr_temp:missing_value = 1.e+38f ;
              tr_temp:long_name = "ADCP transducer temperature" ;
              tr_temp:units = "Celsius" ;
              tr_temp:C_format = "%4.1f" ;
              tr_temp:data_min = 16.54848f ;
              tr_temp:data_max = 25.47167f ;
       short num_pings(time) ;
              num pings:long name = "Number of pings averaged per ensemble" ;
              num pings:units = "None" ;
              num_pings:C_format = "%d" ;
              num_pings:data_min = 57s ;
              num_pings:data_max = 133s ;
       float uship(time) ;
              uship:missing_value = 1.e+38f ;
              uship:long_name = "Ship zonal velocity component" ;
              uship:units = "meter second-1" ;
              uship:C_format = "%9.4f"
              uship:data_min = -6.182626f ;
              uship:data_max = 6.228781f ;
       float vship(time) ;
              vship:missing_value = 1.e+38f ;
              vship:long_name = "Ship meridional velocity component" ;
              vship:units = "meter second-1" ;
              vship:C_format = "%9.4f" ;
              vship:data_min = -6.104665f ;
              vship:data_max = 5.946519f ;
// global attributes:
              :featureType = "trajectoryProfile" ;
              :history = "Created: 2022-06-30 00:55:23 UTC" ;
              :Conventions = "COARDS" ;
              :software = "pycurrents" ;
              :hg_changeset = "3211:63370479787a" ;
              :title = "Shipboard ADCP velocity profiles" ;
              :description = "Shipboard ADCP velocity profiles from in2022_v02 using instrument os75nb -
Short Version." ;
              :cruise_id = "in2022_v02" ;
              :sonar = "os75nb" ;
              :yearbase = 2022 ;
              :ship_name = "RV_Investigator" ;
              :CODAS_variables = "\n",
                     "Variables in this CODAS short-form Netcdf file are intended for most end-user\n",
                     "scientific analysis and display purposes. For additional information see \n ,
                     "the CODAS_processing_note global attribute and the attributes of eachn",
                     "of the variables.\n",
                     "\n",
                     "\n",
                     "time
                                 Time at the end of the ensemble, days from start of year.n",
                     "lon, lat Longitude, Latitude from GPS at the end of the ensemble.\n",
                     "u,v
                                   Ocean zonal and meridional velocity component profiles.\n",
                     "uship, vship Zonal and meridional velocity components of the ship.n",
                     "heading Mean ship heading during the ensemble.\n",
                     "depth
                                  Bin centers in nominal meters (no sound speed profile correction).\n",
                     "tr_temp
                                  ADCP transducer temperature.\n",
                                   Percent Good pings for u, v averaging after editing.n,
                     pq"
                                   Profile Flags based on editing, used to mask u, v.\n",
                     "pflag
                     "amp
                                   Received signal strength in ADCP-specific units; no correction\n",
                                   for spreading or attenuation.\n",
                     "-----\n",
                     "\n",
                     "";
              :CODAS_processing_note = "\n",
                     "CODAS processing note:\n",
                     "======\n",
                     "\n",
                     "Overview\n",
                     "----\n",
                     "The CODAS database is a specialized storage format designed forn",
                     "shipboard ADCP data. \"CODAS processing\" uses this format to hold\n",
                     "averaged shipboard ADCP velocities and other variables, during then,
```

"stages of data processing. The CODAS database stores velocity\n", "profiles relative to the ship as east and north components along withn", "position, ship speed, heading, and other variables. The netCDF \*short\*\n", "form contains ocean velocities relative to earth, time, position, \n", "transducer temperature, and ship heading; these are designed to ben", "\"ready for immediate use\". The netCDF \*long\* form is just a dump of\n", "the entire CODAS database. Some variables are no longer used, and all\n", "have names derived from their original CODAS names, dating back to then, "late 1980\'s.\n", "\n", "Post-processing\n", "----\n" "CODAS post-processing, i.e. that which occurs after the single-ping\n", "profiles have been vector-averaged and loaded into the CODAS database, \n", "includes editing (using automated algorithms and manual tools), $\n$ ", "rotation and scaling of the measured velocities, and application of an", "time-varying heading correction. Additional algorithms developed more\n", "recently include translation of the GPS positions to the transducern, "location, and averaging of ship\'s speed over the times of valid pingsn", "when Percent Good is reduced. Such post-processing is needed prior to\n", "submission of "processed ADCP data " to JASADCP or other archives.<math>n", "\n", "Full CODAS processing\n", "-----\n" "Whenever single-ping data have been recorded, full CODAS processing\n", "provides the best end product.\n", "\n", "Full CODAS processing starts with the single-ping velocities in beam\n", "coordinates. Based on the transducer orientation relative to the\n" "hull, the beam velocities are transformed to horizontal, vertical, and n , "\"error velocity\" components. Using a reliable heading (typically from\n", "the ship\'s gyro compass), the velocities in ship coordinates are\n", "rotated into earth coordinates.\n", "\n", "Pings are grouped into an \"ensemble\" (usually 2-5 minutes duration)\n", "and undergo a suite of automated editing algorithms (removal ofn", "acoustic interference; identification of the bottom; editing based onn", "thresholds; and specialized editing that targets CTD wire interference $\n$ ", "and \"weak, biased profiles\". The ensemble of single-ping velocities\n", "is then averaged using an iterative reference layer averaging scheme.\n", "Each ensemble is approximated as a single function of depth, with a n", "zero-average over a reference layer plus a reference layer velocity\n", "for each ping. Adding the average of the single-ping reference layern", "velocities to the function of depth yields the ensemble-averagen", "velocity profile. These averaged profiles, along with ancillary\n", "measurements, are written to disk, and subsequently loaded into the $\n"$ , "CODAS database. Everything after this stage is \"post-processing\".\n", "\n", "note (time):\n", "----\n" "Time is stored in the database using UTC Year, Month, Day, Hour, n", "Minute, Seconds. Floating point time \"Decimal Day\" is the floating n", "point interval in days since the start of the year, usually the yearn, "of the first day of the cruise.\n", "\n", "∖n", "note (heading):\n", "----\n", "CODAS processing uses heading from a reliable device, and (if\n", "available) uses a time-dependent correction by an accurate headingn, "device. The reliable heading device is typically a gyro compass (forn, "example, the Bridge gyro). Accurate heading devices can be POSMV,n", "Seapath, Phins, Hydrins, MAHRS, or various Ashtech devices; this n, "varies with the technology of the time. It is always confusing to\n", "keep track of the sign of the heading correction. Headings are written\n", "degrees, positive clockwise. setting up some variables:\n", "\n", "X = transducer angle (CONFIG1\_heading\_bias)n", positive clockwise (beam 3 angle relative to ship)\n", "G = Reliable heading (gyrocompass)\n", "A = Accurate headingn". "dh = G - A = time-dependent heading correction (ANCIL2\_watrk\_hd\_misalign) n, "\n", "Rotation of the measured velocities into the correct coordinate system $\n",$ "amounts to  $(u+i^*v)^*(exp(i^*theta))$  where theta is the sum of the\n", "corrected heading and the transducer angle.n", "\n",

```
"theta = X + (G - dh) = X + G - dh n",
"∖n",
"\n",
"Watertrack and Bottomtrack calibrations give an indication of the \n ,
"residual angle offset to apply, for example if mean and median of the\n",
"phase are all 0.5 (then R=0.5). Using the \"rotate" command, n",
"the value of R is added to \"ANCIL2_watrk_hd_misalign\".\n",
"\n",
"new_dh = dh + R \setminus n",
"\n",
"Therefore the total angle used in rotation isn",
"\n",
"new_theta = X + G - dh_{new}n",
       = X + G - (dh + R) \n",
= (X - R) + (G - dh) \setminus n'',
"∖n",
"The new estimate of the transducer angle is: X - R\n",
"ANCIL2_watrk_hd_misalign contains: dh + R\n",
"\n",
"\n",
"Profile flags\n",
"----\n"
"Profile editing flags are provided for each depth cell:\n",
"\n",
"binary
         decimal
                  below
                          Percent\n",
                 bottom Good
"value
        value
                                   bin\n",
"-----+\n",
"000 0\n",
          1
"001
                                    bad\n",
"010
          2
                           bad\n",
         3
4
5
"011
                                    bad\n",
                           bad
"100
                  bad\n",
"101
                   bad
                                    bad\n",
         6
7
                         bad\n",
bad bad\n",
                   bad
"110
"111
                   bad
"-----+-----+-\n",
"";
```

```
}
```

#### 4.2 in2022\_v02\_os150nb.nc

```
netcdf in2022_v02_os150nb {
dimensions:
       time = 8023 ;
       depth_cell = 60 ;
variables:
       int trajectory ;
              trajectory:standard_name = "trajectory_id" ;
       double time(time) ;
               time:long_name = "Decimal day" ;
               time:units = "days since 2022-01-01 00:00:00" ;
               time:C_format = "%12.5f" ;
               time:standard_name = "time" ;
               time:data_min = 76.9597800925926 ;
               time:data_max = 107.938298611111 ;
       double lon(time) ;
               lon:missing_value = 1.e+38 ;
               lon:long_name = "Longitude" ;
               lon:units = "degrees_east" ;
               lon:C_format = "%9.4f" ;
               lon:standard_name = "longitude" ;
               lon:data_min = 147.352172222222 ;
               lon:data_max = 181.4337666666667 ;
       double lat(time) ;
               lat:missing_value = 1.e+38 ;
               lat:long_name = "Latitude" ;
               lat:units = "degrees_north" ;
               lat:C_format = "%9.4f" ;
               lat:standard_name = "latitude" ;
               lat:data_min = -43.2839777777778 ;
               lat:data_max = -29.7338805555556 ;
       float depth(time, depth_cell) ;
               depth:missing_value = 1.e+38f ;
               depth:long_name = "Depth" ;
               depth:units = "meter" ;
```

depth:C format = "%8.2f" ; depth:positive = "down" ; depth:data\_min = 17.93f ; depth:data\_max = 489.99f ; float u(time, depth\_cell) ; u:missing\_value = 1.e+38f ; u:long\_name = "Zonal velocity component" ; u:units = "meter second-1" ; u:C\_format = "%7.2f" ; u:data\_min = -0.6345077f ; u:data\_max = 0.7725085f ; float v(time, depth\_cell) ; v:missing\_value = 1.e+38f ; v:long name = "Meridional velocity component" ; v:units = "meter second-1" ; v:C\_format = "%7.2f" ; v:data\_min = -0.8112372f ; v:data\_max = 0.7708341f ; short amp(time, depth\_cell) ; amp:missing\_value = 32767s ; amp:long\_name = "Received signal strength" ; amp:C\_format = "%d" ; amp:data\_min = 24s ; amp:data\_max = 228s ; byte pg(time, depth\_cell) ; pg:missing\_value = -1b ; pg:long\_name = "Percent good pings" ; pg:C\_format = "%d" ; pg:data\_min = 0b ; pg:data\_max = 100b ; byte pflag(time, depth\_cell) ; pflag:long\_name = "Editing flags" ; pflag:C\_format = "%d" ; pflag:data\_min = 0b ; pflag:data\_max = 6b ; float heading(time) ; heading:missing\_value = 1.e+38f ; heading:long\_name = "Ship heading" ; heading:units = "degrees" heading:C\_format = "%6.1f" ; heading: $data_min = -179.9458f$ ; heading:data\_max = 179.9041f ; float tr\_temp(time) ; tr\_temp:missing\_value = 1.e+38f ; tr\_temp:long\_name = "ADCP transducer temperature" ; tr\_temp:units = "Celsius" ; tr\_temp:C\_format = "%4.1f" ; tr\_temp:data\_min = 16.41768f ; tr\_temp:data\_max = 25.30769f ; short num\_pings(time) ; num\_pings:long\_name = "Number of pings averaged per ensemble" ; num\_pings:units = "None" ; num\_pings:C\_format = "%d" ; num\_pings:data\_min = 101s ; num\_pings:data\_max = 251s ; float uship(time) ; uship:missing\_value = 1.e+38f ; uship:long\_name = "Ship zonal velocity component" ; uship:units = "meter second-1" ; uship:C\_format = "%9.4f" ; uship:data\_min = -6.179954f ; uship:data\_max = 6.227494f; float vship(time) ; vship:missing\_value = 1.e+38f ; vship:long\_name = "Ship meridional velocity component" ; vship:units = "meter second-1" ; vship:C\_format = "%9.4f" ; vship:data\_min = -6.042077f ; vship:data\_max = 5.949365f ; // global attributes: :featureType = "trajectoryProfile" ; :history = "Created: 2022-06-30 00:57:24 UTC" ; :Conventions = "COARDS" ; :software = "pycurrents" :hg\_changeset = "3211:63370479787a"; :title = "Shipboard ADCP velocity profiles" ;

```
:description = "Shipboard ADCP velocity profiles from in2022 v02 using instrument os150nb -
Short Version." ;
               :cruise_id = "in2022_v02" ;
               :sonar = "os150nb" ;
               :yearbase = 2022 ;
               :ship_name = "RV_Investigator" ;
               :CODAS variables = "\n",
                      "Variables in this CODAS short-form Netcdf file are intended for most end-usern,
                      "scientific analysis and display purposes. For additional information see\n",
                      "the CODAS_processing_note global attribute and the attributes of eachn",
                      "of the variables.\n",
                      "∖n",
                      "\n".
                      "-----\n",
                      "time
                                    Time at the end of the ensemble, days from start of year.n,
                      "lon, lat
                                    Longitude, Latitude from GPS at the end of the ensemble.\n",
                                   Ocean zonal and meridional velocity component profiles.\n",
                      "u.v
                      "uship, vship Zonal and meridional velocity components of the ship.\n",
                      "heading
                                   Mean ship heading during the ensemble.n,
                      "depth
                                    Bin centers in nominal meters (no sound speed profile correction).\n",
                      "tr_temp
                                     ADCP transducer temperature.\n",
                      "pg
                                    Percent Good pings for u, v averaging after editing.\n",
                                     Profile Flags based on editing, used to mask u, v.\n",
                      "pflag
                      "amp
                                    Received signal strength in ADCP-specific units; no correction\n",
                                    for spreading or attenuation.\n",
                      "\n",
                      "";
               :CODAS_processing_note = "n",
                      "CODAS processing note:\n",
                      "\n",
                      "Overview\n",
                      "----\n"
                      "The CODAS database is a specialized storage format designed for\n"
                      "shipboard ADCP data. \"CODAS processing\" uses this format to hold\n",
                      "averaged shipboard ADCP velocities and other variables, during the n ,
                      "stages of data processing. The CODAS database stores velocity\n",
                      "profiles relative to the ship as east and north components along withn",
                      "position, ship speed, heading, and other variables. The netCDF *short*\n",
                      "form contains ocean velocities relative to earth, time, position, n",
                      "transducer temperature, and ship heading; these are designed to be\n"
                      "\"ready for immediate use\". The netCDF *long* form is just a dump of n, "the entire CODAS database. Some variables are no longer used, and all n,"
                      "have names derived from their original CODAS names, dating back to the n",
                      "late 1980\'s.\n",
                      "\n",
                      "Post-processing\n",
                        -----\n"
                      "CODAS post-processing, i.e. that which occurs after the single-pingn",
                      "profiles have been vector-averaged and loaded into the CODAS database,\n,
                      "includes editing (using automated algorithms and manual tools),\n",
                      "rotation and scaling of the measured velocities, and application of a n,
                      "time-varying heading correction. Additional algorithms developed more n", "recently include translation of the GPS positions to the transducer n",
                      "location, and averaging of ship\'s speed over the times of valid pingsn",
                      "when Percent Good is reduced. Such post-processing is needed prior ton",
                      "submission of \"processed ADCP data \" to JASADCP or other archives.<math>n",
                      "\n",
                      "Full CODAS processing\n",
                      "_____
                                    ----\n",
                      "Whenever single-ping data have been recorded, full CODAS processing\n",
                      "provides the best end product.\n",
                      "\n",
                      "Full CODAS processing starts with the single-ping velocities in beamn,
                      "coordinates. Based on the transducer orientation relative to the\n",
                      "hull, the beam velocities are transformed to horizontal, vertical, andn",
                      "\"error velocity\" components. Using a reliable heading (typically from\n",
                      "the ship\'s gyro compass), the velocities in ship coordinates are
\n",
                      "rotated into earth coordinates.\n",
                      "\n",
                      "Pings are grouped into an <code>\"ensemble\"</code> (usually 2-5 minutes duration)<code>\n"</code>,
                      "and undergo a suite of automated editing algorithms (removal of\n"
                      "acoustic interference; identification of the bottom; editing based on n",
                      "thresholds; and specialized editing that targets CTD wire interference\n",
                      "and \"weak, biased profiles". The ensemble of single-ping velocities n",
                      "is then averaged using an iterative reference layer averaging scheme.\n",
```

```
"Each ensemble is approximated as a single function of depth, with a \n",
"zero-average over a reference layer plus a reference layer velocity\n",
"for each ping. Adding the average of the single-ping reference layern",
"velocities to the function of depth yields the ensemble-average n",
"velocity profile. These averaged profiles, along with ancillary\n",
"measurements, are written to disk, and subsequently loaded into then",
"CODAS database. Everything after this stage is \"post-processing\".\n",
"\n",
"note (time):\n",
"----\n"
"Time is stored in the database using UTC Year, Month, Day, Hour,n",
"Minute, Seconds. Floating point time \"Decimal Day\" is the floating\n",
"point interval in days since the start of the year, usually the year\n",
"of the first day of the cruise.n",
"\n",
"\n",
"note (heading):\n",
"----\n".
"CODAS processing uses heading from a reliable device, and (ifn",
"available) uses a time-dependent correction by an accurate headingn,
"device. The reliable heading device is typically a gyro compass (for \",
"example, the Bridge gyro). Accurate heading devices can be POSMV,n",
"Seapath, Phins, Hydrins, MAHRS, or various Ashtech devices; thisn",
"varies with the technology of the time. It is always confusing to\n",
"keep track of the sign of the heading correction. Headings are writtenn,
"degrees, positive clockwise. setting up some variables:\n",
"\n",
"X = transducer angle (CONFIG1_heading_bias)\n",
    positive clockwise (beam 3 angle relative to ship)\n",
"G = Reliable heading (gyrocompass)n",
"A = Accurate heading\n",
"dh = G - A = time-dependent heading correction (ANCIL2_watrk_hd_misalign)n",
"\n",
"Rotation of the measured velocities into the correct coordinate system\n",
"amounts to (u+i*v)*(exp(i*theta)) where theta is the sum of then,
"corrected heading and the transducer angle.\n",
"\n",
"theta = X + (G - dh) = X + G - dh \n",
"\n",
"\n",
"Watertrack and Bottomtrack calibrations give an indication of the \n ,
"residual angle offset to apply, for example if mean and median of the\n",
"phase are all 0.5 (then R=0.5). Using the \"rotate" command, n",
"the value of R is added to \"ANCIL2_watrk_hd_misalign\".\n",
"\n",
"new_dh = dh + R \setminus n",
"\n".
"Therefore the total angle used in rotation isn",
"\n",
"new_theta = X + G - dh_new n",
"
         = X + G - (dh + R) \setminus n",
= (X - R) + (G - dh) \n",
"\n",
"The new estimate of the transducer angle is: X - R n",
"ANCIL2_watrk_hd_misalign contains: dh + R\n",
"\n",
"-----\n",
"\n",
"Profile flags\n",
"-----\n"
"Profile editing flags are provided for each depth cell:\n",
"\n",
"binary
          decimal
                    below
                             Percent\n",
                                       bin\n",
"value
         value
                   bottom Good
"-----+------
                 -+----
                                     +----+\n",
"000
          0\n",
"001
            1
                                        bad\n",
                              bad\n",
"010
           2
"011
          3
                              bad
                                       bad\n",
"100
           4
                     bad\n",
          5
                              bad\n",
bad\n",
___+
"101
                     bad
     6
"110
                     bad
"111
           7
                     bad
"-----+\n",
"";
```

}