

RV Investigator

Underway Data Processing Summary Report

Voyage #:	IN2022_V09
Voyage title:	Valuing Australia's new Gascoyne Marine Park
Depart:	Henderson, WA, 00:00 UTC, 19 th November 2022
Return:	Henderson, WA, 07:00 UTC, 19 th December 2022
Data dates:	18-Nov-2022 21:16:45 to 19-Dec-2022 07:09:20
Chief Scientist:	John Keesing (CSIRO)
Data processed by:	Vito Dirita (CSIRO MNF Data Acquisition and Processing)
Report Updated:	31 March 2023

Document History

Date	Version	Author	Comments
31 March 2023	1.0	V. Dirita	Release Version



1.1 Table of Contents

1.1 Table of Contents	2
1.2 Summary	3
1.3 Voyage Track	3
1.4 Underway Data.....	3
1.5 Completeness and Data Quality	4
1.6 Processing Comments	4
1.7 Final Underway Data	8
1.8 Final Dataset Files.....	9
1.9 References.....	9
1.10 APPENDIX:	10

1.2 Summary

The Gascoyne region of Australia's seafloor was identified for protection as an area of national significance and has been proclaimed as a marine park since 2013. The Gascoyne marine park lies in an area with great but poorly known biological diversity and potential for economic development. This voyage will determine the diversity of fishes and of key habitat forming and mobile marine invertebrates across the range of depth regions in the marine park. The data collected during the survey provides descriptions of the physical and biological habitat types in the marine park and will form the basis for future monitoring and reviews of marine park performance and zoning.

1.3 Voyage Track



1.4 Underway Data

Navigation data is acquired using the Seapath 330 plus position and reference unit, which is also differentially corrected by data from the FUGRO marine cstar 3610 receiver.

The Meteorological data consists of two port/starboard relative humidity and temperature sensors, vane type wind sensor, Licor light sensor and barometric air pressure.

Data from the Integrated Marine Observing System sensors (IMOS) are also included. The sensors are port and starboard radiometers and pyranometers, ultrasonic wind speed and direction.

Refer to this voyage's Electronics (SIT) report for instruments used and their serial numbers.

Navigation, meteorological, IMOS and TSG data are preliminary quality controlled by combining all data from hourly recorded files to 5-second values in a NetCDF formatted file. The combined data is referred to as: “underway data”.

A combined file was made on 30th January 2023 by running the Java application UWYMerger (V1.8.1) with a data time range of 18-Nov-2022 21:16:45 - 19-Dec-2022 07:09:20 (UTC), Techsas1 was used as the data source.

Further, it should be noted that the merged data file contains additional underway instrument sensor data that are not quality controlled or processed and is provided for completeness only. This includes data from the air sampling instruments (i.e. two Ozone sensors, Absorption Photometer, Picarro and sampling inlet bearing), pCO₂, Drop keel position, depth and gyro.

For further description of instruments, their respective locations on the vessel and Underway NetCDF variables please refer to the Appendix at the end of this report.

1.5 Completeness and Data Quality

Navigation data (latitude and longitude, speed over ground, ship heading and course over ground); meteorological data (port and starboard for each of air temperature, relative humidity, relative and true wind speed and direction, PAR light, rain and atmospheric pressure) and IMOS data (port and starboard radiometers and pyranometers, ultrasonic relative wind direction and speed), Thermosalinograph (salinity and water temperature) data were evaluated and quality controlled. It should be noted that the underway NetCDF file contains the raw unQC'd data. Therefore even though the QC'd variable may have been set to NaN or otherwise adjusted or filtered, the raw data variable is always available in the NetCDF underway file. This is useful if the end user wishes to apply a different QC or filtering methodology.

1.6 Processing Comments

Atmospheric Pressure: No issues were found with the barometric sensor. The foremast digital barometer was used.

Air Temperature: Minor discrepancies between the port and starboard air temperature sensors were noted (max difference 0.23C°), otherwise both sensors gave very close readings. These discrepancies usually occur during periods of rapid temperature change. This phenomenon has probably come about due to the rapid warming of the ship's metal structure and air due to the ship becoming stationary or cooling of the air temperature due to the ship speeding off from stationary or the evaporation of rainwater around the sensor housing. Furthermore, they also seem to relate to when the ship is stationary with little wind or during/following periods of rainfall or as the result of a change in the ship speed that could be the result of hot exhaust gases being blown over the sensors depending on the wind direction.

Latitude/Longitude: Some missing points (approximately 12,000) were re-instated using the NMEA data strings for both the latitude and longitude.

Humidity: No issues were found with the humidity sensors, please note that minor differences between the port and starboard sensors are mostly the result of minor temperature variations, furthermore, as the accuracy of the instruments is reduced near the equatorial regions these differences are more prominent.

Rain: No major issues were found with the rain gauges, only a small section of the port rain sensor was flagged as suspect (duration of approximately 2 minutes). The disdrometer was used for comparison.

Wind Speed: It has been observed that due to the location of the port wind sensor relative to the ship's superstructure, the instrument could experience some interference when the wind direction is approximately from the starboard stern side (appx. 130 degrees) which would result in greater fluctuations in both speed and direction measurements. Likewise, the starboard wind speed and direction sensor could experience similar interference when the wind direction is approximately from the portside stern (appx. 240 degrees). Under these conditions, if the wind direction is near 130 or 240 degrees and the wind speed measurement has abruptly reduced by more than 10 knots due to the superstructure interference, then the corresponding sensor data is flagged as bad and set to NaN for either port or starboard respectively.

Wind Direction: An automated filter was used to remove data spikes and applied to both the port and starboard (true and relative) wind direction. The filter was applied only in a few selected regions which appeared to be very noisy or spiky. The majority of the spikes appeared to have been correctly flagged and removed. However, with automated filtering, a very small percentage of data points may have been misidentified. The automated filter removes data spikes greater than 1.5 standard deviations (appx. 90 degrees) from the moving average.

CourseOG: Position and velocity (speedOG) are measured by differential GNSS using phase-smoothed pseudo-range and Doppler observations. When using high-precision differential correction a worldwide accuracy of 10 -20 cm is possible.

Course Over Ground (COG) describes the direction of motion with respect to the ground that a vessel has moved relative to the geographic north pole. Accordingly, should a vessel be stationary, it is not travelling a course (e.g., at the wharf).

Under conditions where a vessel is experiencing leeway (wind, current), a vessel's heading and COG may differ. This difference will typically be the largest for vessels moving at slow speeds. When the ship speed is less than 0.5 knots (25.7 cm/s) course overground values are seen to fluctuate and are highly variable. Course and speed overground were recomputed from 5-second latitude and longitude values (truncated to 7 decimal places, 0.000001 degree = 11.112 cm).

The resulting course overground values were compared to the original GPS-derived values and agreed well, (i.e. a slight smoothing was achieved when the ship was underway and when the ship was almost stationary the result was similarly variable). The course overground data for this voyage has not been filtered and has been flagged as good.

speedOG: Missing points (approximately 12,000) were re-instated from the NMEA data strings.

shipHeading: Approximately 12,000 missing data points near the end of the voyage.

PAR: A number of points were marked as suspect for both port and starboard PAR sensors, flatlined regions have been set to NaN.

Pyranometer: A number of points were marked as suspect for the port and starboard pyranometers, flatlined regions have been set to NaN. Please note that night-time observations can result in small negative offset readings (-3.7W/m^2), these readings are within the specifications and acceptable range of the instrument.

Radiometer: No issues were found with the radiometer data, several small flatlined regions have been set to NaN.

Ultrasonic Wind Speed: No issues were found with the ultrasonic wind speed sensor. An automated filter was used which removes spikes greater than 1.5 standard deviations (appx. 12 knots) from the moving average.

Ultrasonic Wind Direction: The relative wind direction values for the ultrasonic wind sensor showed unusual characteristics. This was investigated and it appears that when the wind, more or less, is on the stern of the ship the ultrasonic wind direction values exhibit wild variations (i.e. large spikes) which are not manifested by the two vane-type wind sensors to the same extent. This characteristic is believed to be most likely caused by the interaction of the ship's superstructure/foremast/ship motion and the wind in relation to the ultrasonic wind sensor. An automated filter was used which removes spikes greater than 1.5 standard deviations (appx. 90 degrees) from the moving average.

Water Temperature: No issues were found with the water temperature.

Salinity: The TSG pump was switched off for approximately 7 hours at the start of the voyage to avoid cell contamination and is therefore flagged as missing.

TSG Calibration: During the voyage, bottle salinity samples were collected from the underway seawater supply at regular (every few days) intervals, and the precise time of the sample was recorded. A total of 20 samples were collected and analyzed using a laboratory salinometer. These values were compared with the underway salinity measured by the TSG at the same precise date and time which was used to calculate a scaling coefficient for the TSG using Multiple Linear Regression. This resulted in a scaling coefficient of 1.0004065. The residual had a standard deviation (S.D) of 0.020031 PSU (required 0.01 PSU). This was then applied to the salinity data and its QC flags were set to {'good', 'manually adjusted', 'no error', salinityQC values of 48}. Salinity bottle calibration data may be found in the following file: in2022_V09_TSGCal_BottleResults.csv.

TSG Lag: Examination and comparison of the TSG water temperature profile against the sea surface water temperature showed a lag of approximately about 2.00 minutes between the two data sets and a mean thermal increase of +0.209C° from the intake keel to the TSG. This lag is due to the time taken for the water to travel from the water intake on the port drop keel (where sea surface water temperature is measured) to the TSG located in the underway seawater lab on the ship (where the TSG sensor temperature and the conductivity is measured). When the precise location for the TSG salinity measurement is critical, this lag would need to be taken into account to determine the exact geolocation of the sampled value. For example, assuming a ship's cruising speed of 10 knots and a lag of 2.00 minutes, the salinity measurements could be for a location about 617 meters away from the current ship location. Please note that the TSG and SBE38 SST intakes are located on the port drop keel, the intake depths are described in Appendix [Table 3](#).

Depth: Depth data is no longer processed as part of the underway data set. The non-QC'd data is available in the underway data. The QC'd depth data could be obtained from the processed GSM dataset (centre beam) for this voyage.

Other Data Sets:

It should be noted that the underway NetCDF file contains the raw unQC'd data. Therefore, even though the QC'd variable may have been set to NaN or otherwise adjusted or filtered, the raw data variable is always available in the QC'd underway file. This is useful if the end-user wishes to apply a different QC or filtering methodology.

Comparing Port and Starboard Sensors:

The following table compares the mean-absolute-difference and max-absolute-differences between port and starboard sensor outputs before and after QC has been applied. Please note that the **After QC:** column only accounts for values that are flagged as good.

Sensor:	Before QC		After QC:		Units:
	mean(abs(diff))	max(abs(diff))	mean(abs(diff))	max(abs(diff))	
Air Temp	0.23	1.1	0.23	1.1	<i>Degree Celsius</i>
Humidity	1.1	7.6	1.1	7.6	<i>%RH</i>
relWindSpeed	1.44	20.2	1.34	19.19	<i>knot</i>
trueWindSpeed	1.47	20.46	1.38	19.86	<i>knot</i>
relWindDir	4.9	179.99	4.74	177.84	<i>Degree</i>
trueWindDir	4.5	178.79	4.49	146.36	<i>Degree</i>
PAR	29.02	1714	23.15	1595	<i>$\mu E/m^2/s$</i>
Pyranometer	19.6	1016.7	16.04	818	<i>W/m^2</i>
Radiometer	3.7	28.1	3.7	28.1	<i>W/m^2</i>
Rain	0.01	0.6	0.01	0.4	<i>mm</i>

Table.1 Comparing Port and Starboard sensors before and after QC

Commonly Used QC Flags:

The datasets include quality control (QC) flags which are described in more detail in the references provided, normally however only a small subset is used, below are the most commonly used QC flags. Please note that on some systems and file formats, eg. NetCDF, it is not possible to store unsigned byte values. In this case, flags greater than 127 are stored as negative numbers. To convert them to unsigned integers, simply add 256.

QC Flags Description					
Signed	Unsigned	Description	Data State	Operation Type	Error Type
-123	133	Bad (data is set to NaN)	Bad	None	Error Flagged by processor
0	0	Good	Good	None	No error, data is good
-187	69	Suspect (data	Suspect	None	Error flagged by processor
-135	121	Operator adjusted	Suspect	Manually adjusted	Data out of range
-115	141	Data missing	Bad	None	No data, missing for an unknown reason
-53	203	not QC'd	No QC	None	Preliminary processing (calibration) only
-199	57	Operator adjusted	Good	Manually Adjusted	Data out of range
-208	48	Re-calibrated	Good	Manually Adjusted	None

Table.2 QC Flags: numeric values and description

1.7 Final Underway Data:

The navigation, meteorological and Thermosalinograph data will be entered into the O&A divisional data warehouse. All data timestamps are in UTC.

Final Underway (csv) QC'd Data							
	Parameter Name:	parameterQC:	% Good	% Sus	% Bad	% Missing	Units
1	latitude	latitudeQC	99.98	0	0	0.02	Deg North
2	longitude	longitudeQC	99.98	0	0	0.02	Deg East
3	speedOG	speedOGQC	99.98	0	0	0.02	knot
4	courseOG	courseOGQC	99.98	0	0	0.02	degree
5	shipHeading	shipHeadingQC	97.68	0	0	2.32	degree
6	portAirTemp	portAirTempQC	99.98	0	0	0.02	Celsius
7	stbdAirTemp	stbdAirTempQC	99.98	0	0	0.02	Celsius
8	portHumidity	portHumidityQC	99.98	0	0	0.02	%
9	stbdHumidity:	stbdHumidityQC	99.98	0	0	0.02	%
10	atmPressure:	atmPressureQC	99.98	0	0	0.02	mbar
11	portRelWindDir	portRelWindDirQC	99.82	0.05	0.11	0.02	degree
12	stbdRelWindDir	stbdRelWindDirQC	99.89	0.02	0.07	0.02	degree
13	portTrueWindDir	portTrueWindDirQC	99.97	0.01	0	0.02	degree
14	stbdTrueWindDir	stbdTrueWindDirQC	99.97	0	0	0.02	degree
15	portRelWindSpeed	portRelWindSpeedQC	99.58	0.03	0.37	0.02	knot
16	stbdRelWindSpeed	stbdRelWindSpeedQC	99.26	0	0.72	0.02	knot
17	portTrueWindSpeed	portTrueWindSpeedQC	99.68	0.01	0.29	0.02	knot
18	stbdTrueWindSpeed	stbdTrueWindSpeedQC	99.37	0	0.61	0.02	knot
19	maxWindGust	maxWindGustQC	99.91	0	0.07	0.02	knot
20	portRain	portRainQC	99.97	0.01	0	0.02	mm
21	stbdRain	stbdRainQC	99.98	0	0	0.02	mm
22	portPAR	portPARQC	99.81	0.13	0.04	0.02	uE/m ² /s
23	stbdPAR	stbdPARQC	99.22	0.72	0.04	0.02	uE/m ² /s
24	portPyranometer	portPyranometerQC	99.89	0	0.09	0.02	W/m ²
25	stbdPyranometer	stbdPyranometerQC	99.06	0.88	0.04	0.02	W/m ²
26	portRadiometer	portRadiometerQC	99.88	0	0.1	0.02	W/m ²
27	stbdRadiometer	stbdRadiometerQC	99.94	0	0.04	0.02	W/m ²
28	ultrasonicRelWindSpeed	ultrasonicRelWindSpeedQC	98.02	0	1.95	0.02	knot
29	ultrasonicTrueWindSpeed	ultrasonicTrueWindSpeedQC	98.91	0	1.06	0.02	knot
30	ultrasonicRelWindDir	ultrasonicRelWindDirQC	99.47	0.07	0.43	0.02	degree
31	ultrasonicTrueWindDir	ultrasonicTrueWindDirQC	99.91	0	0.06	0.02	degree
32	salinity	salinityQC	98.23	0	0.73	1.04	PSU
33	waterTemp	waterTempQC	99.97	0	0	0.03	Celsius

Table.3 Overall data quality results summary

1.8 Final Dataset Files

The final datasets for publication and distribution:

Final Dataset Files	
IN2022_V09uwy5sec.csv	5-second resolution CSV format dataset of QC'd parameters
IN2022_V09uwy10sec.csv	10-second resolution CSV format (interpolated) dataset of QC'd parameters
IN2022_V09uwy1min.csv	1-minute resolution CSV format (interpolated) dataset of QC'd parameters
IN2022_V09uwy5min.csv	5-minute resolution CSV format (interpolated) dataset of QC'd parameters
IN2022_V09uwy.nc	5-second resolution NetCDF format full dataset including unQC'd data
in2022_v09_TSGCal_BottleResults.csv	TSG bottle Salinity calibration results

1.9 References and Links

Subversion repository version of DPG Matlab generic tools 3974

Pender, L., 2000. Data Quality Control flags.

1.10 APPENDIX:

TABLE-1: Underway Sensors

The table below contains the description of Ship sensors and Underway NetCDF variables.

Underway Data Instrument and Identifier	Sensor Description	Position	NetCDF variable	QC	Variable Description	Variable units
Navigation Instruments:						
Seapath 330+ with Seatex MRU 5+ and FUGRO Seastar 3610 DGNSS receiver	DGPS system providing position, attitude, velocity, acceleration and timing information.	Monkey Island & Bridge equipment room				
			Longitude	yes	Longitude	Degree East
			Latitude	yes	Latitude	Degree North
			speedOG	yes	Ship speed overground	Knot
			courseOG	yes	Ship course overground	Degree
			shipHeading	yes	Heading of the ship	Degree
			alt	no	Altitude re: mean sea level (geoid)	Metres
Northrup Grumman Sperry 4914-CA Navigat X MK1	Gyrocompass	Bridge				
			gyroHeading	No	Gyro Heading	Degree
Kongsberg Maritime Skipper DL850	3 Axis doppler log - measuring vessel speed through water	Gondola	(no data)			
			longitudinalWaterSpeed	No	Longitudinal water speed	knot
			transverseWaterSpeed	No	Transversal water speed	knot
			longitudinalGroundSpeed	No	Longitudinal ground speed	knot
			transverseGroundSpeed	No	Transversal ground speed	knot
			lockOnWater	No	Lock on water flag	n/a
			lockonGround	No	Lock on the ground flag	n/a
Sea Water Instruments:						
Sea-Bird-SBE 21 TSG	Thermosalinograph (TSG)	CTD Space				
			salinity	Yes	Measures sea surface salinity	Practical Salinity Units (PSU)
			tsgSensorTemp	No	Water temperature measurement in the TSG canister	Degree Celsius (degC)
Burkert 8045	Flow meter	CTD space				
			tsgFlow	No	Flow rate of seawater through the TSG	l/min
Burkert 8045	Flow meter	Underway Seawater Lab				
			labMainFlow	No	Underway lab main seawater flow rate	l/min
Kobold MIK-C	Flow meter	Underway Seawater Lab				
			labBranchFlow	No	Underway lab branch seawater flow rate	l/min
Sea-Bird - SBE 38	Remote Temperature Probe	Port Drop Keel				

			waterTemp	Yes	Sea surface water temperature measurement	Degree Celsius (degC)
Wet Labs Wetstar Fluorometer	Fluorometer	Underway Seawater Lab				
			fluorescence	No	Measures active phytoplankton biomass and chlorophyll concentrations	Percentage of the full scale voltage
CSIRO Hobart pCO2	Underway pCO ₂ system measuring surface water CO ₂ mole fraction	Underway Seawater Lab				
			equTemp	No	Equilibrator water temperature	Degree Celsius (degC)
			XCO2	No	XCO2	ppm
			waterVapour	No	Water vapour	mmol/mole
			licorPressure	No	Licor pressure	hPa
			equPressure	No	Equilibrator pressure	hPa
			waterFlow	No	Water flow	l/min
			licorFlow	No	Licor flow	ml/min
			ventFlow	No	Vent Flow	ml/min
			condTemp	No	Condenser Temperature	Degree Celsius (degC)
			pumpSpeed	No	CO2 Pump Speed	l/min
Aanderaa Oxygen Optode 3835	Oxygen Sensor	Underway Seawater Lab				
			do		oxygen	uM
			doSaturation		Air saturation	Percentage (%)
			optodeWaterTemp		Optode water temperature	Degrees Celsius (degC)
CSIRO Drop keel sensor	Measuring drop keel draft	Port & starboard				
			portKeelExtension		Port drop keel extension	meters
			starboardKeelExtension		Starboard drop keel extension	meters
Met Instruments:						
Rotronic T&RH HC2A-S3	Temperature and Humidity Sensor	Foremast (Starboard)				
			stbdAirTemp	Yes	Starboard air temperature measurement	Degree Celsius (degC)
			stbdHumidity	Yes	Starboard humidity measurement	Percentage (%)
			stbdDewPoint	Yes	Starboard Dew Point	Degree Celsius (degC)
Rotronic T&RH HC2A-S3	Temperature and Humidity Sensor	Foremast (Port)				
			portAirTemp	Yes	Port air temperature measurement	Degree Celsius (degC)
			portHumidity	Yes	Port humidity measurement	Percentage (%)
			portDewPoint	Yes	Port Dew Point	Degree Celsius (degC)
Vaisala Ship's Barometer PTB330	Atmospheric pressure	Bridge Wing	atmPressureBridge	Yes	Atmospheric pressure measurement	Millibar (mbar)
Vaisala Ship's Barometer PTB330	Atmospheric pressure	Foremast	atmPressure	Yes	Atmospheric pressure measurement	Millibar (mbar)

RM Young Wind Sensor Type 05107	Vane type wind sensor	Foremast (Port)				
			portRelWindSpeed	Yes	Wind speed relative to the ship	knot
			portRelWindDir	Yes	Wind direction relative to the ship	Degree
			portTrueWindSpeed	Yes	True wind speed, corrected for ship speed	knot
			portTrueWindDir	Yes	True wind direction, corrected for ship heading	Degree
			maxWindGust	Yes	True maximum wind gust corrected for ship speed	knot
RM Young Wind Sensor Type 05108	Vane type wind sensor	Foremast (Starboard)				
			stbdRelWindSpeed	Yes	Wind speed relative to the ship	knot
			stbdRelWindDir	Yes	Wind direction relative to the ship	Degree
			stbdTrueWindSpeed	Yes	True wind speed, corrected for ship speed	knot
			stbdTrueWindDir	Yes	True wind direction, corrected for ship heading	Degree
Gill WindObserver II	Ultrasonic Wind Sensor	Foremast (Port)				
			ultrasonicRelWindSpeed	Yes	Wind speed relative to the ship	knot
			ultrasonicRelWindDir	Yes	Wind direction relative to the ship	Degree
			ultrasonicTrueWindSpeed	Yes	True wind speed, corrected for ship speed and direction	knot
			ultrasonicTrueWindDir	Yes	True wind direction, corrected for ship speed and heading	Degree
RM Young Rain Gauge type 50202	Syphoning Rain Sensor	Foremast				
			portRain	Yes	Accumulated hourly rain	mm
			stbdRain	Yes	Accumulated hourly rain	mm
Eppley PIR	Precision Infrared Radiometer	Monkey Island (Starboard)				
			stbdRadiometer	Yes	Measure radiation in the band 4-100 micron, longwave radiation	W/m ²
Eppley PIR	Precision Infrared Radiometer	Monkey Island (Port)				
			portRadiometer	Yes	Measure radiation in the band 4-100 micron, longwave radiation	W/m ²
Eppley PSP	Precision Spectral Pyranometer	Monkey Island (Starboard)				
			stbdPyranometer	Yes	Measure radiation in the band 0.2 - 4 micron, shortwave radiation	W/m ²
Eppley PSP	Precision Infrared Radiometer	Monkey Island (Port)				
			portPyranometer	Yes	Measure radiation in the band 0.2 - 4 micron, shortwave radiation.	W/m ²

LI-COR LI-190 Quantum Sensor	Photosynthetically Active Radiation	Monkey Island (Starboard)				
			stbdPAR	Yes	measures radiation in the photosynthetically active region of 0.4-0.7 micron	uE/m^2/s
LI-COR LI-190 Quantum Sensor	Photosynthetically Active Radiation	Monkey Island (Port)				
			portPAR	Yes	measures radiation in the photosynthetically active region of 0.4-0.7 micron	uE/m^2/s
Uni-Southampton ISAR SST	Radiation sea surface temperature	Bridge Wing (Port)				
			isarWaterTemp	No	ISAR Water Temperature	Degree Celsius (degC)

Air Sampling Systems:

CSIRO air sampling inlet	Air inlet controller	foremast				
			inletBearing	No	Air sampling inlet bearing	degree
			trackingBearing	No	Tracking target bearing	degree
Thermo Scientific MAAP Model 5102	Multi-angle Absorption Photometer (MAAP)	Aerosol Lab (air sampling inlet)				
			blackCarbonConc	No	Concentration of black carbon	ug/m^3
			airFlow	No	Air flow rate	Litre per Hour (L/h)
Thermo Scientific Model 49i Ozone Analyzer	Ozone Monitor					
			o3Ozone1	No	Ozone measurement	ppb
			ozone1Meterflags	No	Instrument specific quality flag	n/a
Thermo Scientific Model 49i Ozone Analyzer	Ozone Monitor					
			o3Ozone2	No	Ozone measurement	ppb
			ozone2Meterflags	No	Instrument specific quality flag	n/a
Picarro Model G2301 CRDS Analyzer	Greenhouse Gas Spectrometer CO2, CH4, H2O Near IR Laser					
			co2Dry	No	CO2 dry concentration	ppm
			ch4Dry	No	CH4 dry concentration	ppm
			H2O	No	Water concentration percentage	Dimensionless

Depth:

Kongsberg EM122 multibeam sounder		Gondola	depth	No	Water depth,	meters
Kongsberg EM710 multibeam sounder		Gondola	depth	No	Water depth,	meters
EK60, 18KHz sounder		Port Drop Keel	Depth, (if not provided by EM122 or EM710)	No	Water depth	meters

TABLE-2: Location of Meteorological Instruments:

Date:	26/03/2019					
Surveyors:	Stuart Edwards					
	Matt Boyd					
	CSIRO GSM Team					
Instrument:	Leica TCRP 1205+ Total Station AND extrapolation from drawings					
Sensors surveyed with respect to existing vessel coordinate system:						
	X-axis is positive toward starboard and perpendicular to Y -axis					
	Y-axis is positive forward and parallel to vessel centreline keel					
	Z-axis is positive upwards					
CRP is MRU5+ located in transceiver room on 1st platform deck						
MRU5+ is 2.066m to Starboard of the V/L centreline & 53.439m fwd from transom. (Obtained from Parker Maritime)						
Δ H of Load Line measured from 02 level with Plumbob and tape, 9m from 02 Deck. Height of 02 deck calculated to be 8.707m above CRP on 1st Plat deck. Load Line height datum below vessel CRP						
ID	Description	X	Y	Z	Comment	Final Height Above Summer Load Line
LL	Summer Load Line	7.222	-10.695	-0.293	Waterline reference	0.000
WS1	Foremast Propeller Anemometer Stbd	-0.513	35.811	24.487	Measured to base of sensor	24.780
WS2	Foremast Propeller Anemometer Port	-3.361	35.867	24.228	Measured to base of sensor	24.521
WS3	Foremast Gill Ultrasonic Anemometer	-3.344	35.986	21.812	Measured to base of sensor	22.105
WS4	Precipitation Sensor Siphoning Port (formerly called "Central")	-2.621	35.999	21.260	Measured to base of sensor	21.553
WS10	Monkey Island Radiometer Plate Stbd	-0.164	-0.430	24.980	Measured to centre bottom face of disc	25.273
WS11	Monkey Island Radiometer Plate Port	-3.753	-0.389	24.927	Measured to centre bottom face of disc	25.220
WS12	Bridge Digital Barometer	-1.559	-4.243	20.265	Measured to centre of unit	20.558
WS13	SST Radiometer (Port Bridge Wing)	-11.77	-3.3	19.3	Measured to centre of bottle (Taped Measurement)	19.593
	Foremast T&RH Sensor (Port)	-2.636	35.1	24.451	Relative measurements and estimates from drawings	24.744
	Foremast T&RH Sensor (Starboard)	-1.253	35.101	24.451	Relative measurements and estimates from drawings	24.744
	Precipitation Sensor Siphoning (Starboard)	-1.241	35.101	21.260	Relative measurements and estimates from drawings	21.553
	Foremast Digital Barometer	-3.316	32.596	9.61	Relative measurements and estimates from drawings	9.903

TABLE-3: Drop Keel Data

	Reference Point	Vertical Offset in metres (positive up)			
Drop Keel Position		Flush with Hull	Flush with gondola	Intermediate	Fully extracted
Drop Keel Extension	Base of Hull	0.00	-1.194	-2.00	-4.00
Base of Hull	Ship's Central reference Point (CRP)	-6.54			
Base of Drop Keel	CRP	-6.54	-7.73	-8.54	-10.54
SBE38 SST Intake	Base of Drop Keel	0.30			
SBE38 SST Intake	CRP	-6.24	-7.43	-8.24	-10.24
Summer Load Line (SLL)	CRP	-0.29			
SBE38 SST Intake	SLL (ie Depth below waterline)	-5.95	-7.14	-7.95	-9.95
TSG Intake	Base of Drop Keel	0.54			
TSG Intake	CRP	-6.00	-7.19	-8.00	-10.00
TSG Intake	SLL (ie Depth below the waterline)	-5.71	-6.90	-7.71	-9.71